

Air Impacttools™ | composite



2235QTiMAX 1/2" Ring type
CCN: 47517574001



- MAX POWER with 1,220 Nm of maximum torque in reverse and 1,760 Nm of nut busting torque
- MAX DURABILITY with the titanium hammercase, the steel-wear plate and composite housing
- MAX RELIABILITY backed by a two-year warranty

2235QTiMAX-2 50mm extended anvil, CCN: 47517884001
2235M-BOOT Protection Boot
CCN: 47520153001

2235QXPA 1/2" Ring type
CCN:47532836001



- 1,220 Nm of maximum torque in reverse and 1,760 Nm of nut-busting torque
- Quiet technology
- Only 2,1 kg

2235QXPA-BOOT Protection Boot
CCN:

2135QXPA 1/2" Ring type
CCN:47517913001



- 1,057 Nm of maximum torque in reverse and 1,490 Nm of nut busting torque
- Quiet technology
- Only 1.80 kg
- 4-position power regulator and 1-hand forward and reverse switch

2135QXPA-2 50mm extended anvil, CCN: 47517914001
2135M-BOOT Protection Boot
CCN: 45545977

Ref.	CCN	in	Nm	Nm	rpm	bpm	kg	mm	in	mm	l/s	l/s	dB(A)	m/s ² /K ⁽¹⁾
2235QTiMAX	47517574001	1/2" <input type="checkbox"/>	1,220	1180	8,500	1,220	2.10	193	1/4 NPT	10	3.0	11.30	91.9	9.0/2.8
2235QTI-MAX-2	47517884001	1/2" <input type="checkbox"/>	1,220	1180	8,500	1,220	2.10	244	1/4 NPT	10	3.0	11.30	91.9	7.7/2.7
2235QXPA	47532836001	1/2" <input type="checkbox"/>	1,220	1180	8,500	1,220	2.10	193	1/4 NPT	10	3.0	11.30	91.9	9.0/2.8
2135QXPA	47517913001	1/2" <input type="checkbox"/>	1,057	746	9,800	1,250	1.80	187	1/4 NPT	10	2.7	10.80	90.7	13.3/4.6
2135QXPA-2	47517914001	1/2" <input type="checkbox"/>	1,057	746	9,800	1,250	1.90	241	1/4 NPT	10	2.7	10.80	90.7	9.7/1.8
2130XP	80136112	1/2" <input type="checkbox"/>	816	474	9,500	1,200	1.90	187	1/4 NPT	10	2.1	10.40	94.3	8.9/2.0
2130XP-TL	46812251	1/2" <input type="checkbox"/>	816	75	7,800	1,150	1.90	187	1/4 NPT	10	2.1	14.20	94.4	10.0/1.5

2235QTiMAX-10SK 10 sockets kit
CCN: 47521865001
2135QXPA + Impact Sockets 1/2" (10, 11, 12, 13, 14, 17, 19, 21, 22, and 24 mm)



2235QTiMAX-3SK 3 long sockets kit
CCN: 47521867001

2135QXPA + Long Impact Sockets, insulated, thin-wall 1/2" (17, 19, and 21 mm)

2130XP+SK4M3L 3 long sockets kit
CCN: 17021346
2135QXPA + Long Impact Sockets, insulated, thin-wall 1/2" (17, 19, and 21 mm)



2130XP-K 10 sockets kit
CCN: 16985301
2135QXPA + Impact Sockets 1/2" (10, 11, 12, 13, 14, 17, 19, 21, 22, and 24 mm)

2130XP 1/2" Ring type
CCN:80136112



- 816 Nm maximum torque in reverse
- Ergonomic composite housing is lightweight, protects from cold air, and offers great operator comfort
- Full-stroke tease throttle
- Multi-position power management and easy glide forward/reverse switch

2135QXPA-10SK 10 sockets kit
CCN: 47521891001
2135QXPA + Impact Sockets 1/2" (10, 11, 12, 13, 14, 17, 19, 21, 22, and 24 mm)

2135QXPA-3SK 3 long sockets kit
CCN: 47521896001 2135QXPA + Long Impact Sockets, insulated, thin-wall 1/2" (17, 19, and 21 mm)



2130XP-TL 1/2" Ring type / Torque Limited at 75 Nm, CCN: 46812251

2130M-BOOT Protection Boot
CCN: 45505369

⁽¹⁾ ISO28927 – 3-axis measurement: vibration level/measurement uncertainty.
Performance at 6.2 bar (90 psi)