

TBN Preset Breaking Torque Wrenches

Torque range from 0.4 to 200 N.m

TBN Preset Breaking Torque Wrenches are robust production tools that reduce the chance of over-tightening, because of the unique Breaking Mechanism. They can be used for a wide range of applications, with

a choice of compatible interchangeable end fittings. Their durable yet compact design makes them easy to use in restricted spaces in any manufacturing or maintenance environment.



Breaking Mechanism

Incorrect tightening is unlikely



INDUSTRY SECTORS

Maintenance & Repair



Military

Manufacturing



Automotive



Aerospace



Electronics



Military



Consumer Products

TBN Preset Breaking Torque Wrenches

TBN 2, 10, 25, 65, 135 & 200



Improved accuracy, consistency and control. Accurate process control is ensured by reducing the risk of under and over tightening, due to unique Breaking Technology. This gives the operator more time to react once the target torque is reached

Compact slimline design. This maximises productivity in restricted space applications

Compatible End Fittings. A range of interchangeable end fittings is available, making this an extremely versatile tool.

Ease of use. Tools can be used with confidence by operators at any skill level, due to the unique Breaking Technology

Increased production efficiency. Increased operator comfort and productivity, from the ergonomic design, that includes lightweight materials and moulded handgrip

Long tool life. High quality, robust design and construction minimise tool replacement and downtime costs

Rectangular fitting version also available. **See table below**

Additional features

TBN 2 and 10 Wrenches will be supplied with a Calibration Certificate when ordered with an attached end fitting and pre-set

For EPA options, **see table below**

For Further Information on any of these Products please email : Sales@appliedtorque.co.uk

Order Code	Model	Range		Drive	k mm	kg	Repeatability	ISO 6789 Class	ISO 9001
		ISO	Imperial						
011100	TBN 2	0.4-2 N.m	3.5-18 lbfin	Captive Pin	105	0.11	+/- 6%	2C	✓
011110	TBN 2 G	0.4-2 N.m	3.5-18 lbfin		133	0.13	+/- 6%	2C	✓
011200	TBN 10	1-10 N.m	9-89 lbfin	Captive Pin	105	0.13	+/- 6%	2C	✓
011210	TBN 10 G	1-10 N.m	9-89 lbfin		133	0.15	+/- 6%	2C	✓
050000	TBN 25	5-25 N.m	4-18 lbfft		265	0.41	+/- 4%	2C	✗
050010	TBN 25 G	5-25 N.m	4-18 lbfft		265	0.41	+/- 4%	2C	✗
050100	TBN 65	10-65 N.m	7-48 lbfft		302	0.75	+/- 4%	2C	✗
050110	TBN 65 G	10-65 N.m	7-48 lbfft		302	0.75	+/- 4%	2C	✗
050200	TBN 135	27-135 N.m	18-100 lbfft		408	1.03	+/- 4%	2C	✗
050210	TBN 135 G	27-135 N.m	18-100 lbfft		408	1.03	+/- 4%	2C	✗
050300	TBN 200	40-200 N.m	29-147 lbfft		520	1.40	+/- 4%	2C	✗
050310	TBN 200 G	40-200 N.m	29-147 lbfft		520	1.40	+/- 4%	2C	✗