



This economical light-duty 3/8" Impactool™ is ideal for general service work including engine repair, sump removal, exhaust and transmission work.

- ◆ 136 Nm (100 ft-lb) of maximum torque.
- ◆ Pin-type impact mechanism.
- ◆ One-hand forward and reverse lever.
- ◆ Wide power regulator settings in forward and reverse.

Specifications at 6.2 bar (90 PSI)

Part number	LA158
Ordering number	49825870
Drive size (square)	3/8 in
PERFORMANCE	
Working torque	5 - 75 ft-lb / 7 - 100 Nm
Maximum torque	100 ft-lb / 136 Nm
Recommended fastener size	7/16 in / M11
Maximum free speed	10 000 rpm
Impacts per minute	1 400
AIR SYSTEM	
Air inlet (NPTF)	1/4 in
Minimum hose size	3/8 in / 10 mm
Average air consumption	4 cfm / 113 l/min
Air consumption at load	16 cfm / 453 l/min
NOISE & VIBRATIONS	
Sound pressure / power	88.4 / 99.4 dB(A)
Vibration level (ISO8662)	1.9 m/s²
WEIGHT & DIMENSIONS	
Tool weight	2.75 lb / 1.25 kg
Tool dimensions (l x w x h)	137 x 163 x 50 mm
Shipping weight	3.08 lb / 1.40 kg
Shipping dimensions (l x w x h)	150 x 180 x 55 mm
UPC/EAN Code	Not available