



The Ingersoll Rand 2135QXPA Series Impactool™ was built on the hardworking and respected foundation laid by the 2135TiMAX. The result is a light, quiet and powerful impact wrench that delivers an incredible level of performance and power at a cost that won't punish your wallet. The 2135QXPA is the finely tuned and finely crafted impact wrench you need to tackle the toughest jobs.

- 1 057 Nm (780 ft-lb) of maximum torque in reverse.
- Ingersoll Rand TwinHammer impact mechanism is the strongest, most durable and longest life mechanism in the industry.
- Unique reverse-bias 7-vane motor delivers even more power in reverse.
- Ergonomic composite housing is lightweight, protects from cold air and offers great operator comfort.
- Feather-touch trigger allows precise delivery of power and speed.
- 4-position power regulator in forward helps adjusting the power to the application.
- One-hand forward/reverse switch for easy operation.
- 360° swivel inlet helps eliminating twisted hoses.
- Patented technology reduces the noise level without sacrificing the power.
- Optional piped-away exhaust system can further reduce noise level and directs air away from the operator.

Specifications at 6.2 bar (90 psi)

Part Number	2135QXPA
Ordering number	47517913001
Drive size (square)	1/2 in
Torque settings (forward / reverse)	4 / 1
Other available versions:	
- kit with 10 short sockets	2135QXPA-10SK
- kit with 3 long sockets	2135QXPA-3SK

PERFORMANCE

Maximum torque in forward	700 ft-lb / 949 Nm
Maximum torque in reverse	780 ft-lb / 1 057 Nm
Recommended fastener size	M14 in / 9/16
Free speed	11 000 rpm
Impacts per minute	1 250

AIR SYSTEM

Air Inlet (NPT)	1/4 in
Minimum hose size	3/8 in / 10 mm
Average air consumption	5.8 CFM / 164 L/min
Air consumption at load	23.0 CFM / 651 L/min
Impacting sound pressure / power (ISO15744)	90.7 / 101.7 dB(A)
Free speed sound pressure / power (ISO15744)	86.0 / 97.0 dB(A)
Vibration level / measurement uncertainty (ISO28927)	13.3 / 4.6 m/s ²

WEIGHT & DIMENSIONS

Tool weight	4.0 lb / 1.80 kg
Tool dimensions (L x W x H)	189 x 69 x 182 mm
Shipping weight	4.8 lb / 2.2 kg
Shipping dimensions (L x W x H)	216 x 242 x 84 mm
UPC / EAN code	6 63023 120102
Origin	Assembled in the USA





SK4M3L
81287377
1/2" Impact socket set (3 pcs) (17, 19 and 21 mm)



SK4M14
81287351
1/2" Impact socket set (14 pcs) (10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 23 and 24 mm)



Impact sockets
For the complete range, see our accessory catalogue.

04706388
2131-366
Horizontal hanger



2115-K284
45612637
Piped-away exhaust kit



33104
91486330
Hose whip, 1/4" NPT, 6 mm inside diameter, 30 cm (1 ft)



77NMC2
88104070
7N7/7S7 Series nipple, 1/4" male thread, 7.2 mm bore (EURO 7.2 - 7.4)



Filters, regulators, lubricators
For the complete range, see our accessory catalogue.



115-LBK1
04616108
Lubricant kit for Impacttools™ with composite housing



2135-THK1
80119571
Impact mechanism service kit



SK4M5L
81287369
1/2" Impact socket set (5 pcs) (17, 19, 21, 22 and 24 mm)



SK4M18
81287385
1/2" Impact socket set (18 pcs) (10, 11, 13, 14, 17, 19, 21, 22, 24, 13L, 14L, 21L, 24L, 17L, 19L and 21L mm, extension 125 mm)



4UA9
03070216
1/2" right-angle head (speed reduction: 25% torque output reduction: up to 50%)



2135-BOOT
45505377
Protective tool boot



IB6NMC2
88103015
IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)



Quick Release Couplings
For the complete range, see our accessory catalogue.



10Z4
03875671
Oil, Class 1, no. 10, 0.12 L



2135-TK2
45535028
Motor service kit