

Pro

Pro Preset Torque Screwdrivers

Torque range from 0.05 to 13.5 N.m

Versatile Preset Torque Application Screwdrivers for any manufacturing environment

These tools complement our traditional accuracy, durability and quality with the benefits of a moulded plastic body and enhanced ergonomic design

Durable, versatile and lightweight tools that can be used for Assembly, Maintenance and Servicing in any engineering or manufacturing environment

Pro 450 and 1350 models come with T-Bars as standard to assist with higher torque

To allow for customisation and clear identification interchangeable coloured end caps are available in packs of four (Order Code: 065800)



Pro 25 & 150



Pro 450 & 1350



T-Bar

Slipping Mechanism
Incorrect tightening is impossible



ESD Preset Torque Screwdrivers

Torque range from 0.05 to 13.5 N.m

Preset Torque Application Screwdrivers for electronic component assembly

The ESD Preset Torque Screwdriver range is ideal for safe electronic component assembly as these tools are EPA compliant

Tools that complement our traditional accuracy, durability and quality with the benefits of a moulded plastic body and enhanced ergonomic design

ESD 450 and 1350 models come with T-Bars as standard to assist with higher torque

To allow for customisation and clear identification interchangeable coloured end caps are available in packs of four (Order Code: 065800)





Slipping Mechanism
Incorrect tightening is impossible



ESD 25 & 150

ESD 450 & 1350



For Further Information Please Email : sales@appliedtorque.co.uk

Order Code	Gedore Ref	Model	Range		Drive	k	mm	g	Repeatability	ISO 6789 Class	T-Bar	
			ISO	Imperial							✓	✗
065400	2927756	Pro 25 FH	0.05 - 0.25 N.m	0.45 - 2.2 lbf.in	$\frac{1}{4}$	132	210	+/- 6%	2F	✗	✗	
065500	2927764	Pro 150 FH	0.2 - 1.5 N.m	1.8 - 13 lbf.in	$\frac{1}{4}$	132	210	+/- 6%	2F	✗	✗	
065600	2927772	Pro 450 FH	0.5 - 4.5 N.m	4.5 - 40 lbf.in	$\frac{1}{4}$	140	230	+/- 6%	2F	✓	✗	
065700	2927780	Pro 1350 FH	2.5 - 13.5 N.m	22 - 120 lbf.in	$\frac{1}{4}$	140	230	+/- 6%	2F	✓	✗	
065405	2927799	ESD 25 FH	0.05 - 0.25 N.m	0.45 - 2.2 lbf.in	$\frac{1}{4}$	132	210	+/- 6%	2F	✗	✓	
065505	2927802	ESD 150 FH	0.2 - 1.5 N.m	1.8 - 13 lbf.in	$\frac{1}{4}$	132	210	+/- 6%	2F	✗	✓	
065605	2927810	ESD 450 FH	0.5 - 4.5 N.m	4.5 - 40 lbf.in	$\frac{1}{4}$	140	230	+/- 6%	2F	✓	✓	
065705	2927829	ESD 1350 FH	2.5 - 13.5 N.m	22 - 120 lbf.in	$\frac{1}{4}$	140	230	+/- 6%	2F	✓	✓	
065800	Pack of four interchangeable coloured end caps ●●●●											