

# Angle Air Nutrunners

Adjustable Shut-Off

## 1 Series


*Time-tested design provides repeatable results day in and day out at an economical price.*

### Features

- Torque Range: 3.5 – 46.0 in-lbs (0.4 – 5.2 Nm)
- Speeds: 700 rpm
- Compact and lightweight
- Coated grip for operator comfort
- 1/4" quick change or square drive options
- Recommended for applications where precise torque control is required



1RLN2S3



Adjustable Shut-Off Clutch

### Service and Accessories

#### Manuals:

- 16574568
- 80167380
- 16575250





#### Accessories:

Spring balancer: BLD1  
Spindle accessories, see page 183

#### Kits:

Tune up kit: 0-TK2

Model	in-lbs (Nm)	in-lbs (Nm)	in-lbs (Nm)	rpm	lbs (kg)	in (mm)	in (mm)	in (mm)	in
<b>DC LEVER START</b>									
1RLN2S5	3.5 – 23.0 (0.4 – 2.6)	7.1 – 34.5 (0.8 – 3.9)	9.7 – 46.0 (1.1 – 5.2)	700	1.7 (0.8)	12.5" (318)	0.52" (13.2)	1.3" (33)	1/4" □
1RLN2S3	3.5 – 23.0 (0.4 – 2.6)	7.1 – 34.5 (0.8 – 3.9)	9.7 – 46.0 (1.1 – 5.2)	700	1.7 (0.8)	12.5" (318)	0.52" (13.2)	1.3" (33)	1/4" ○

Series				
1	73 dBA	1/8" NPT	1/4" (6 mm)	13 cfm (368 L/min)