



Ingersoll Rand has always stood for innovative solutions that help make your job easier. Now we've taken our most economical 1/2" impact - the 236 - and packed it with more power, impressive features, and durability, giving you the highest quality for all your general service applications at an affordable price. The 236 delivers 610 Nm (450 ft-lb) of maximum torque with a free speed of 7,400 rpm, so no matter what job you're doing, this tool will get it done reliably and economically.

- ◆ Durable single hammer impact mechanism reduces overall length for easier access to tough-to-reach places.
- ◆ Two piece construction for convenient motor accessibility and serviceability.
- ♦ Easy-to-use forward / reverse power regulator delivers the right amount of power you need for the job.

Specifications at 6.2 bar (90 PSI)

Part number 236
Ordering number 80171879
Drive size (square) 1/2 in

PERFORMANCE

Working torque 25 - 200 ft-lb / 34 - 271 Nm Maximum torque 450 ft-lb / 610 Nm Recommended fastener size 9/16 in / M14 Maximum free speed 7 400 rpm Impacts per minute 1 200

AIR SYSTEM

Air inlet (NPTF)1/4 inMinimum hose size3/8 in / 10 mmAverage air consumption4.3 cfm / 122 l/minAir consumption at load24 cfm / 680 l/min

NOISE & VIBRATIONS

Sound pressure / power 90.3 / 101.3 dB(A)
Vibration level (ISO8662) 5.9 m/s²

WEIGHT & DIMENSIONS

 Tool weight
 5.30 lb / 2.40 kg

 Tool length
 7.09 in / 180 mm

 Shipping weight
 6.00 lb / 2.70 kg

 Shipping dimensions (l x w x h)
 240 x 215 x 83 mm

 UPC/EAN Code
 6 63023 02097 6

