

Dial Measuring Torque Wrenches

Torque range from 0.8 to 2000 N.m



The Gedore Torque range of Dial Measuring Torque Wrenches is designed to verify or monitor torque, in order to ensure process conformity, product safety and absolute reliability. The main pointer on the dial captures the finishing torque applied to a fastener with a memory pointer. These low cost, durable and versatile tools can be used for Maintenance, Repair, Quality Control and Assembly in any engineering or manufacturing environment.



Durable storage case for ADS and BDS models



ADS, BDS, CDS, DDS & EDS
Signal versions available. All ADS models are EPA compliant

Robust and versatile tools Dial Measuring Torque Wrenches

- Dual scale.** Dial provides effective measurement in Metric and Imperial torque units in both directions, delivering flexibility and minimising tool investment
- Ease of use.** Tools can be used by operators at any skill level
- Long tool life.** High quality construction and robust design with a two year warranty

- No risk of tool damage.** Overload Protection System, Recessed dial minimises damage to the dial display
- Versatile usage.** Use for Maintenance, Repair, Assembly and Quality Control
- Wide range of applications.** Tightening and untightening measurement is possible, with double-ended ratchet as standard (except EDS versions)

Additional features

- Calibration Service enables tools to be kept accurate and up to date. **See page 98**
- Special extension spanners. **See page 95**
- Optional audio visual signal system. Clear indication is given when the target torque has been reached

For more information: Tool Selector; gedore-torque.com/tool-selector Telephone; +44 (0) 1483 894 476
Videos; www.youtube.com/gedore-torque Email; salesandrepairs@gedore-torque.com



Order Code	Model	ISO		Imperial		Drive	k	mm	kg	Accuracy	ISO 6789 Class	Signal
		N.m	lb.ft	N.m	lb.ft							
010100	ADS 4	0.8-4.0 N.m	0.1 N.m	7-35 lb.ft	1 lb.ft	1/4"	244	0.52	+/- 3%	1B	X	✓
010108	ADS 4 S	0.8-4.0 N.m	0.1 N.m	7-35 lb.ft	1 lb.ft	1/4"	244	0.52	+/- 3%	1B	✓	✓
010120	ADS 8	1.6-8.0 N.m	0.25 N.m	14-75 lb.ft	1 lb.ft	1/4"	244	0.52	+/- 3%	1B	X	✓
010128	ADS 8 S	1.6-8.0 N.m	0.25 N.m	14-75 lb.ft	1 lb.ft	1/4"	244	0.52	+/- 3%	1B	✓	✓
010140	ADS 12 D	2.4-12 N.m	0.5 N.m	24-120 lb.ft	2 lb.ft	1/4"	244	0.52	+/- 3%	1B	X	✓
010148	ADS 12 DS	2.4-12 N.m	0.5 N.m	24-120 lb.ft	2 lb.ft	1/4"	244	0.52	+/- 3%	1B	✓	✓
010160	ADS 12 A	2.4-12 N.m	0.5 N.m	24-120 lb.ft	2 lb.ft	1/4"	244	0.52	+/- 3%	1B	X	✓
010168	ADS 12 AS	2.4-12 N.m	0.5 N.m	24-120 lb.ft	2 lb.ft	1/4"	244	0.52	+/- 3%	1B	✓	✓
010180	ADS 25	5-25 N.m	1 N.m	48-240 lb.ft	10 lb.ft	1/4"	244	0.52	+/- 3%	1B	X	✓
010188	ADS 25 S	5-25 N.m	1 N.m	48-240 lb.ft	10 lb.ft	1/4"	244	0.52	+/- 3%	1B	✓	✓
010200	ADS 25 F	5-25 N.m	1 N.m	4-20 lb.ft	0.5 lb.ft	1/4"	244	0.52	+/- 3%	1B	X	✓
010208	ADS 25 FS	5-25 N.m	1 N.m	4-20 lb.ft	0.5 lb.ft	1/4"	244	0.52	+/- 3%	1B	✓	✓
010220	ADS 40	8-40 N.m	1 N.m	72-360 lb.ft	10 lb.ft	1/4"	244	0.52	+/- 3%	1B	X	✓
010228	ADS 40 S	8-40 N.m	1 N.m	72-360 lb.ft	10 lb.ft	1/4"	244	0.52	+/- 3%	1B	✓	✓
010240	ADS 40 F	8-40 N.m	1 N.m	6-30 lb.ft	1 lb.ft	1/4"	244	0.52	+/- 3%	1B	X	✓
010248	ADS 40 FS	8-40 N.m	1 N.m	6-30 lb.ft	1 lb.ft	1/4"	244	0.52	+/- 3%	1B	✓	✓
010300	BDS 80 A	16-80 N.m	2 N.m	12-60 lb.ft	1 lb.ft	1/4"	435	1.35	+/- 3%	1B	X	X
010380	BDS 80 AS	16-80 N.m	2 N.m	12-60 lb.ft	1 lb.ft	1/4"	440	1.47	+/- 3%	1B	✓	X
010320	BDS 80 E	16-80 N.m	2 N.m	12-60 lb.ft	1 lb.ft	1/4"	435	1.36	+/- 3%	1B	X	X
010400	BDS 80 ES	16-80 N.m	2 N.m	12-60 lb.ft	1 lb.ft	1/4"	440	1.49	+/- 3%	1B	✓	X
010410	BDS 100 EF	20-100 N.m	2 N.m	14-70 lb.ft	2 lb.ft	1/4"	515	1.41	+/- 3%	1B	X	X
010415	BDS 100 E	20-100 N.m	2 N.m	168-840 lb.ft	24 lb.ft	1/4"	515	1.41	+/- 3%	1B	X	X
010340	BDS 160	32-160 N.m	2.5 N.m	24-120 lb.ft	2 lb.ft	1/4"	515	1.41	+/- 3%	1B	X	X
010340	BDS 160 S	32-160 N.m	2.5 N.m	24-120 lb.ft	2 lb.ft	1/4"	520	1.54	+/- 3%	1B	✓	X
010360	BDS 200	40-200 N.m	5 N.m	30-160 lb.ft	5 lb.ft	1/4"	515	1.41	+/- 3%	1B	X	X
010440	BDS 200 S	40-200 N.m	5 N.m	30-160 lb.ft	5 lb.ft	1/4"	520	1.54	+/- 3%	1B	✓	X
010520	CDS 400 S	80-400 N.m	10 N.m	60-300 lb.ft	10 lb.ft	1/4"	710	3.20	+/- 3%	1B	✓	X
010620	DDS 800 S	160-800 N.m	20 N.m	120-600 lb.ft	20 lb.ft	1/4"	1000	4.90	+/- 3%	1B	✓	X
010700	EDS 1400 S	280-1400 N.m	25 N.m	200-1000 lb.ft	25 lb.ft	1/4"	2040	16.7	+/- 3%	1B	✓	X
010720	EDS 2000 S	400-2000 N.m	50 N.m	300-1500 lb.ft	50 lb.ft	1/4"	2040	16.7	+/- 3%	1B	✓	X

INDUSTRY SECTORS

- Maintenance & Repair
- Aerospace
- Military
- Utilities
- Quality Control
- Aerospace
- Automotive
- Packaging