

Air Production Drills

Inline

Q2 Series

Compact and lightweight, Q2 drills deliver more power in a smaller package to get the job done in less time.

Features

- Stall Torque: 10.6 33.6 in-lbs (1.2 3.8 Nm) Speeds: 1500 5100 rpm
- · Variable speed control allows slow starting and high speed for fast drilling
- $\boldsymbol{\cdot}$ Excellent power-to-weight ratio gets the job done with less fatigue



QS151D

Service and Accessories

Manuals:

16572752



Accessories:

Horizontal hanger: 3RA-365

Chuck: R0H-99

Spindle accessories, see page 185

Kits:

Tune-up kit: Q2-PDRILL-TK1

| | Max Nm | 1 min. | | | Max. | → | | | |
|---------------|-------------|--------|-----------|------------|----------|-----------|-------------|--|--|
| Model | in-lbs (Nm) | rpm | lbs (kg) | in (mm) | in (mm) | in (mm) | cfm (L/min) | | |
| C LEVER START | | | | | | | | | |
| QS511D | 10.6 (1.2) | 5,100 | 1.4 (0.6) | 8.1" (205) | 1/4" (6) | 0.6" (15) | 16 (450) | | |
| QS381D | 13.3 (1.5) | 3,800 | 1.4 (0.6) | 8.1" (205) | 1/4" (6) | 0.6" (15) | 16 (450) | | |
| QS301D | 16.8 (1.9) | 3,000 | 1.4 (0.6) | 8.1" (205) | 1/4" (6) | 0.6" (15) | 16 (450) | | |
| QS151D | 33.6 (3.8) | 1,500 | 1.4 (0.6) | 8.1" (205) | 1/4" (6) | 0.6" (15) | 16 (450) | | |

| Series | 200 | | | 0 Ø | |
|--------|---------|--------|----------|-------------|---------|
| Q2 | 0.30 hp | 75 dBa | 1/4" NPT | 1/4" (6 mm) | 3/8″-24 |