

1/2" square drive Impactool



Ingersoll Rand has always stood for innovative solutions that help make your job easier. Now we've taken our most economical 1/2" impact - the 236 - and packed it with more power, impressive features, and durability, giving you the highest quality for all your general service applications at an affordable price. The 236 delivers 610 Nm (450 ft-lb) of maximum torque with a free speed of 7,400 rpm, so no matter what job you're doing, this tool will get it done reliably and economically.

- ◆ **Durable single hammer impact mechanism** reduces overall length for easier access to tough-to-reach places.
- ◆ **Two piece construction** for convenient motor accessibility and serviceability.
- ◆ **Easy-to-use forward / reverse power regulator** delivers the right amount of power you need for the job.

Specifications at 6.2 bar (90 PSI)

Part number	236
Ordering number	80171879
Drive size (square)	1/2 in

PERFORMANCE

Working torque	25 - 200 ft-lb / 34 - 271 Nm
Maximum torque	450 ft-lb / 610 Nm
Recommended fastener size	9/16 in / M14
Maximum free speed	7 400 rpm
Impacts per minute	1 200

AIR SYSTEM

Air inlet (NPTF)	1/4 in
Minimum hose size	3/8 in / 10 mm
Average air consumption	4.3 cfm / 122 l/min
Air consumption at load	24 cfm / 680 l/min

NOISE & VIBRATIONS

Sound pressure / power	90.3 / 101.3 dB(A)
Vibration level (ISO8662)	5.9 m/s²

WEIGHT & DIMENSIONS

Tool weight	5.30 lb / 2.40 kg
Tool length	7.09 in / 180 mm
Shipping weight	6.00 lb / 2.70 kg
Shipping dimensions (l x w x h)	240 x 215 x 83 mm
UPC/EAN Code	6 63023 02097 6