

# ATB

## ATB Adjustable Breaking Torque Wrenches

Torque range from 5 to 100 N.m

High quality, versatile, tools that have been designed and engineered to reduce the risk of under and over tightening in Production,

Service and Repair. The Calibrated Scale allows for pre-setting of torque.

ATB 100

ATB 25 showing N.m Scale

**Breaking Mechanism**  
Incorrect tightening is unlikely



### INDUSTRY SECTORS

Maintenance & Repair



Manufacturing



## ATB Adjustable Breaking Torque Wrenches

ATB 25, 50 & 100

**Accuracy and consistency.** Improved process control is ensured by reducing the risk of under and over tightening, due to the unique Breaking Technology

**Calibrated scale.** A visible micrometer style scale allows the user to adjust the tool quickly and easily to their desired torque setting, enabling a range of different torque settings to be applied

**Long tool life.** High quality, durable design and construction, minimises replacement and downtime costs

**Process Control.** Reduces the likelihood of warranty and rework by assuring process control through accurate and repeatable torque application

**Production efficiency.** Improved operator comfort and productivity, from the ergonomic design, which includes lightweight materials and moulded plastic handgrip

**Versatility.** Versatile tools ideal for Maintenance & Repair applications where a range of torques can be applied quickly and easily to a variety of fasteners and connectors

### Additional features

1/4", 3/8" or 1/2" interchangeable ratchet heads come as standard

Available in N.m, lbf.in or lbf.ft versions



For Further Information on any of these Products please  
Email: [sales@appliedtorque.co.uk](mailto:sales@appliedtorque.co.uk)

Order Code	Model	Calibrated Range				Drive	k mm	kg	Accuracy	ISO 6789 Class
		ISO	Imperial	Imperial	Imperial					
050636	ATB 25 D	5-25 N.m	0.1 N.m	-	-	1/4"	345	1.11	+/- 4%	2A
050641	ATB 25 D	-	-	50-250 lbf.in	1 lbf.in	1/4"	345	1.11	+/- 4%	2A
050646	ATB 25 D	-	-	4-20 lbf.ft	0.1 lbf.ft	1/4"	345	1.11	+/- 4%	2A
050638	ATB 25 A	5-25 N.m	0.1 N.m	-	-	3/8"	345	1.12	+/- 4%	2A
050643	ATB 25 A	-	-	50-250 lbf.in	1 lbf.in	3/8"	345	1.12	+/- 4%	2A
050648	ATB 25 A	-	-	4-20 lbf.ft	0.1 lbf.ft	3/8"	345	1.12	+/- 4%	2A
050685	ATB 50	10-50 N.m	0.25 N.m	-	-	3/8"	365	1.14	+/- 4%	2A
050690	ATB 50	-	-	120-440 lbf.in	2 lbf.in	3/8"	365	1.14	+/- 4%	2A
050695	ATB 50	-	-	7-37 lbf.ft	0.125 lbf.ft	3/8"	365	1.14	+/- 4%	2A
050735	ATB 100	20-100 N.m	0.5 N.m	-	-	1/2"	400	1.30	+/- 4%	2A
050740	ATB 100	-	-	240-880 lbf.in	4 lbf.in	1/2"	400	1.30	+/- 4%	2A
050745	ATB 100	-	-	14-74 lbf.ft	0.25 lbf.ft	1/2"	400	1.30	+/- 4%	2A