

Email: sales@appliedtorque.co.uk for further information



This durable in-line Impactool[™] is handy for small cramped spaces common to small engine repair and other general service work.

- 204 Nm (150 ft-lb) of maximum torque.
- Ingersoll Rand JumboHammer impact mechanism is the simplest and the most durable and longest life mechanism in the industry.
- Pressure-feed lubrication system automatically greases the impact mechanism for increased durability and reliability.
- The small size of this tool will allow greater access to tight spaces.
- Wide range of power regulator settings helps adjusting the power to the application.

Specifications at 6.2 bar (90 psi)

Part Number Ordering number Drive size (square)

PERFORMANCE Working torque

Maximum torque Recommended fastener size Free speed Impacts per minute

AIR SYSTEM

Air Inlet (NPTF) Minimum hose size Average air consumption Air consumption at load

NOISE & VIBRATION

Sound pressure / power (ISO15744) Vibration level / measurement uncertainty (ISO28927)

WEIGHT & DIMENSIONS

Tool weight Tool length Shipping weight Shipping dimensions (L x W x H) UPC / EAN code Origin 01197060 3/8 in

211

20 - 125 ft-lb / 27 - 170 Nm 150 in-lb / 204 Nm 7/16 in / M11 10 000 rpm 1 500

211

3/8" ImpactoolTM

1/4 in 3/8 in / 10 mm 2.5 CFM / 71 L/min 11.0 CFM / 311 L/min

> 104.0 / 115.0 dB(A) 5.9 / 1.6 m/s²

2.40 lb / 1.09 kg 6.6 in / 168 mm 3.08 lb / 1.40 kg 215 x 240 x 80 mm 6 62023 00080 0 Made in China

CE

www.ingersollrandproducts.com

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.







SK3M10 81287344

3/8" Impact socket set (10 pcs) (9, 10, 11, 12, 13, 14, 15, 16, 17 and 19 mm)



1901-366 03670163

Horizontal hanger

33104-45 92938760

Hose whip, 1/4" NPT, 6 mm inside diameter, 45 cm (1.5 ft)



77NMC2 88104070 7N7/7S7 Series nipple, 1/4" male thread, 7.2 mm bore (EURO 7.2 - 7.4)

Filters, regulators, lubricators For the complete range, see our accessory catalogue.



105-LBK1 04616090 Lubricant kit for Impactools[™] with metal housing

105-4T-6 04618930 Grease for Impactools hammer mechanism (6 tubes)



211-TK2 03866449 Motor service kit







BMDS-2

92842152

Impact sockets

accessory catalogue.

For the complete range, see our

IB6NMC2 88103015

IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)

Cable balancer, 1-2.5 kg, 2 m (6-1/2 ft)

Quick Release Couplings

For the complete range, see our accessory catalogue.



10Z4 03875671

Oil, Class 1, no. 10, 0.12 L

Lubricants

For the complete range, see our accessory catalogue.

www.ingersollrandproducts.com

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.



