

HandTorque® Standard Series

Model	HT 1/5	HT 2/5	HT 2/25	HT 2/25 AWUR	HT 5/5	HT 5/25	HT 5/25 AWUR	HT 6/5	HT 6/25	HT 6/25 AWUR	HT 6/125 AWUR
Part Number/s	16010	16012.HD	16034.HD	16089.HD	16014	16028	16090	16016	16024	16092	16093
Multiplication Ratio	5:1	5:1	25:1	25:1	5:1	25:1	25:1	5:1	25:1	25:1	125:1
Input Square	½"	¾"	½"	½"	¾"	½"	½"	¾"	½"	½"	½"
Output Square	¾"	1"	1"	1"	1"	1"	1"	1½"	1½"	1½"	1½"
Maximum Torque Output	N-m	1700	1700	1700	1700	3400	3400	3400	3400	3400	3400
	lbf-ft	1254	1254	1254	1254	2508	2508	2508	2508	2508	2508
Dimensions (mm)	∅D	108	108	108	108	119	119	119	119	119	119
	H	83	98	98	114	106	127	132	106	128	159
	L	303	303	303	303	355	355	355	355	355	355
	R1	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	R2 min.	83	83	83	83	86	86	86	86	86	86
	R2 max.	216	216	216	216	263	263	263	263	263	263
Tool Weight (kg)	3	3.2	4.6	6.7	4.7	6.4	7.5	4.7	6.4	7.5	9
Reaction Weight (kg)	2.2	2.2	2.2	2.2	2.5	2.5	2.5	2.5	2.5	2.5	2.5

Model	HT 7/5	HT 7/25	HT 7/25 AWUR	HT 7/125 AWUR	HT 9/25	HT 9/25 AWUR	HT 9/125 AWUR	HT 11/25	HT 11/125 AWUR	HT 12/87.5 AWUR	HT 13/125 AWUR	
Part Number/s	16067	16018	16065	16068	16059	16070	16071	16082	16049	18085	16053	
Multiplication Ratio	5:1	25:1	25:1	125:1	25:1	25:1	125:1	25:1	125:1	87.5:1	125:1	
Input Square	¾"	½"	½"	½"	¾"	¾"	½"	¾"	½"	¾"	¾"	
Output Square	1½"	1½"	1½"	1½"	1½"	1½"	1½"	2½"	2½"	2½"	2½"	
Maximum Torque Output	N-m	6000	6000	6000	9500	9500	9500	20000	20000	34000	47500	
	lbf-ft	4425	4425	4425	7007	7007	7007	14751	14751	25077	35034	
Dimensions (mm)	∅D	144	144	144	184	184	184	212	212	248	315	
	H	136	157	162	188	166	162	182	208	235	322	
	L	423	423	423	423	448	448	448	609	609	325	341
	R1	84	84	84	84	84	84	84	N/A	N/A	N/A	N/A
	R2 min.	150	150	150	150	175	175	175	320	320	N/A	N/A
	R2 max.	331	331	331	331	351	351	351	500	500	N/A	N/A
Tool Weight (kg)	8.1	9.6	10.7	12.2	16.3	17.4	18.9	31.7	32.1	41.5	95.2	
Reaction Weight (kg)	6.3	6.3	6.3	6.3	8.3	8.3	8.3	13.3	13.3	6.5	6.9	

