



Perfect for any maintenance or repair application, the 2115QTiMAX delivers maximum power and control, along with unmatched reliability that comes from more than a century of proven engineering and innovation.

- 407 Nm (300 ft-lb) of maximum torque in reverse - that's the best-in-class performance.
- Ingersoll Rand TwinHammer impact mechanism is the strongest, most durable and longest life mechanism in the industry.
- Titanium hammercase is lightweight with unparalleled durability.
- Unique reverse-bias 7-vane motor delivers even more power in reverse.
- Ergonomic composite housing is lightweight, protects from cold air and offers great operator comfort.
- Feather-touch trigger allows precise delivery of power and speed.
- 4-position power regulator in forward helps adjusting the power to the application.
- One-hand forward/reverse switch for easy operation.
- 360° swivel inlet helps eliminating twisted hoses.
- Patented technology reduces the noise level without sacrificing the power.
- Optional piped-away exhaust system can further reduce noise level and direct air away from the operator.
- FREE two-year limited warranty with tool registration.

Specifications at 6,2 bar (90 psi)

Part Number	2115QTiMAX
Ordering number	45587326
Drive size (square)	3/8 in
Available versions:	
- 1/2" square drive	2125QTiMAX

PERFORMANCE

Working torque in forward	25 - 230 ft-lb / 34 - 312 Nm
Maximum torque in forward	250 ft-lb / 339 Nm
Working torque in reverse	280 ft-lb / 380 Nm
Maximum torque in reverse	300 ft-lb / 407 Nm
Recommended fastener size	7/16 in / M11
Free speed	15 000 rpm
Impacts per minute	1 500

AIR SYSTEM

Air Inlet (NPTF)	1/4 in
Minimum hose size	3/8 in / 10 mm
Average air consumption	4,0 CFM / 113 L/min
Air consumption at load	17,0 CFM / 481 L/min

NOISE & VIBRATION

Impacting sound pressure / power (ISO15744)	93,2 / 104,2 dB(A)
Free speed sound pressure / power (ISO15744)	89,7 / 100,7 dB(A)
Vibration level / measurement uncertainty (ISO28927)	7,5 / 1,8 m/s ²

WEIGHT & DIMENSIONS

Tool weight	2.49 lb / 1,13 kg
Tool dimensions (L x W x H)	151 x 56 x 171 mm
Shipping weight	3.29 lb / 1,50 kg
Shipping dimensions (L x W x H)	238 x 213 x 79 mm
UPC / EAN code	6 63023 04313 5
Origin	Assembled in the USA





SK3M10
81287344
3/8" Impact socket set (10 pcs) (9, 10, 11, 12, 13, 14, 15, 16, 17 and 19 mm)



Impact sockets
For the complete range, see our accessory catalogue.



2112-366
10323350
Horizontal hanger



BMDS-2
92842152
Cable balancer, 1-2,5 kg, 2 m (6-1/2 ft)



2115-BOOT
45505351
Protective tool boot



2115-K284
45612637
Piped-away exhaust kit



IB6NMC2
88103015
IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)



77NMC2
88104070
7N7/7S7 Series nipple, 1/4" male thread, 7,2 mm bore (EURO 7,2 - 7,4)



Quick Release Couplings
For the complete range, see our accessory catalogue.



Filters, regulators, lubricators
For the complete range, see our accessory catalogue.



115-LBK1
04616108
Lubricant kit for Impactools™ with composite housing



10Z4
03875671
Oil, Class 1, no. 10, 0,12 L



115-4T-6
04618948
Grease for Impactools with composite housing (6 tubes)



Lubricants
For the complete range, see our accessory catalogue.



2115-THK2
45585932
Impact mechanism service kit



2115-TK2
45585189
Motor service kit

Please Email: sales@appliedtorque.co.uk for further information on any of these products