

PneuTorque® PTM Series

Technical Data

Model	PTM-52-500-B	PTM-52-800-B	PTM-72-1000-B	PTM-72-1350-B	PTM-72-2000-B	PTM-80-2700-B	PTM-92-4000-B	PTM-92-4000-B	PTM-119-4500-B	PTM-119-6000-B	
Part Number/s	18100.B06	18101.B06	18102.B06	18103.B08	18104.B08	180296.B08	18159.B08	18159.B12	18108.B12	18109.B12	
Torque Range	N-m	100 - 500	160 - 800	200 - 1000	270 - 1350	400 - 2000	540 - 2700	800 - 4000	800 - 4000	900 - 4500	1200 - 6000
	lbf-ft	74 - 370	118 - 590	147 - 738	200 - 1000	295 - 1475	400 - 2000	590 - 2950	590 - 2950	660 - 3300	885 - 4425
Square Drive	¾"	¾"	¾"	1"	1"	1"	1"	1½"	1½"	1½"	
Output Speed (rpm)	224	148	122	86	58	40	32	32	23	15.5	
Dimensions (mm)	∅D	52	52	72	72	72	80	92	92	119	119
	H1	29	29	29	29	29	29	29	29	29	29
	H2	224	224	224	224	224	224	224	224	224	224
	H3	116	116	116	116	116	116	116	116	116	116
	L	310	310	342	342	371	335	394	394	415	415
	R1	59	59	68	68	74	80	87	87	118	118
	R2 min.	71	71	91	91	91	115	115	115	150	150
	R2 max.	131	131	165	165	165	205	205	205	199	199
Tool Weight (kg)	4.1	4.1	6.1	6.1	6.5	7.5	8.5	8.5	13.3	13.3	
Reaction Weight (kg)	0.85	0.85	0.7	0.7	0.7	1.35	1.35	1.35	2.2	2.2	

Note: Also available as forward only tools, in the part number replace B with F when ordering. Deduct 48 mm from dimension 'L' and 0.3 kg from the 'Tool Weight'.

