

▼ Shown from left to right: JHA-356, JHA-156



JH, JHA Series

Capacity:
7 - 150 ton

Stroke:
76 - 155 mm

Maximum Operating Pressure:
700 bar

- All-directional operation on 7, 15 and 35 ton JHA-series
- Internal relief valve to prevent overloading
- Machined flat front and bottom surfaces permit flush alignment in tight corners
- Chrome plated plungers
- Pumping handle included
- Automatic by-pass port to prevent over-extension (JH-series).



Lifting Wedge and Machine Lifts

Ideal to lift the load the first few centimeters. The LW-16 Lifting Wedge requires a very small access gap of only 10 mm.


Page: **172**



Load Skates

For moving heavy loads easily and safely.

Page: **174**

| Style | Jack Capacity ton (kN) | Stroke (mm) | Model Number | Jack Effective Area (cm ²) | Collapsed Height (mm) | Extended Height (mm) | Bottom Plate Dimensions W x L (mm) | Plunger Diameter (mm) | Pump Speed |  (kg) |
|-----------------|---------------------------|----------------|--------------|---|--------------------------|-------------------------|--|--------------------------|------------|---|
| Aluminium Jacks | 7 (62) | 76 | JHA-73 | 9,6 | 133 | 209 | 73 x 158 | 30,2 | Single | 5,0 |
| | 15 (133) | 153 | JHA-156 | 20,3 | 247 | 401 | 92 x 238 | 41,4 | Single | 13,2 |
| | 35 (311) | 155 | JHA-356 | 45,6 | 257 | 412 | 117 x 254 | 54,1 | Single | 18,1 |
| | 75 (667) | 153 | JHA-756 | 102,6 | 285 | 439 | 174 x 325 | 114,3 | Single | 42,6 |
| | 150 (1335) | 155 | JHA-1506 | 197,9 | 327 | 482 | 241 x 407 | 158,8 | 2-Speed | 95,3 |
| Steel Jacks | 30 (267) | 155 | JH-306 | 38,3 | 254 | 409 | 95 x 242 | 69,9 | Single | 26,8 |
| | 50 (445) | 154 | JH-506 | 62,1 | 260 | 414 | 127 x 258 | 88,9 | 2-Speed | 40,8 |
| | 100 (890) | 153 | JH-1006 | 133,1 | 287 | 440 | 181 x 328 | 130,1 | 2-Speed | 74,4 |