

Air 1/4" and 3/8" Impactools™



2115QTIMAX – 3/8" ■ ring type

Accessories: **2115-B00T**
(CCN: 45505351), protective tool boot

- 407 Nm (300 ft-lb)
- Only 1.13 kg and 151 mm
- Twin-hammer impact mechanism
- Titanium hammer case and composite housing
- 4-position power regulator
- 1-hand forward and reverse switch



2115XP – 3/8" ■

Perfect for any maintenance or repair application, the 2115XP delivers plenty of power and superior control, along with unmatched reliability that comes from more than a century of proven engineering and innovation.

Accessories: **2115-B00T**
(CCN: 45505351), protective tool boot

- 370 Nm (407 ft-lb) of maximum torque in reverse
- Only 1.13 kg and 151 mm
- Twin-hammer impact mechanism
- 4-position power regulator and 1-hand forward and reverse switch



212 – 3/8" ●

The classic 212 is one of the most popular Impactools™ in its class. It provides plenty of power and rugged durability in a convenient easy-to-use package.

- 244 Nm (180 ft-lb) of maximum torque
- Pressure-feed lubrication system automatically greases the impact mechanism for increased durability and reliability
- Wide range of power regulator settings helps adjusting the power to the application



LA158 – 3/8" ●

Offers professional technicians performance, comfort and durability with great value for money.

- 136 Nm (100 ft-lb) of maximum torque
- Small size to allow greater access to tight spaces
- Easy glide forward/reverse switch
- Wide range of power regulator settings helps adjusting the power to the application



2102XP – 3/8" ■
2101XP – 1/4" ■

- 68 Nm (50 ft-lb)
- Only 0.6 kg and 165 mm
- Swinging-hammer impact mechanism
- Composite housing
- 1-hand forward and reverse switch



2015MAX – 3/8" ●

- 244 Nm (180 ft-lb)
- Only 1.54 kg
- Jumbo-hammer impact mechanism
- Composite housing
- 2-position power regulator



211 – 3/8" ●

- 204 Nm (150 ft-lb)
- Only 1.09 kg
- Jumbo-hammer impact mechanism
- 5-position power regulator



2168 – 3/8" ●

- 271 Nm (200 ft-lb)
- Only 1.27 kg
- Ball & cam impact mechanism
- Power regulator

Service Kits



	A	B
1105MAX-D2	45668456	45668522
105-D2	45668142	45668522
2115QTIMAX	45565189	45565932
2115XP	45565189	45565932
2015MAX	47100474	47100359
212	03866522	—
211	03866449	—
LA158	49827108	49827090
109XPA	16594160	16594384
107XPA	80146491	16590416
1207MAX-D3	47085931	47086368
1105MAX-D3	45668456	45668563
105-D3	45668142	45668563

Specifications at 6.2 bar (90 psi)

	CCN	Nm	Nm max	rpm	BPM	kg	Length mm	NPTF	L/s	L/2 max	dB(A)	m/s/K ⁽¹⁾	
3/8" ■													
2115QTIMAX	45587326	34 – 312	407	15,000	1,500	1.13	151	1/4"	10	1.9	8.0	93.2	7.5/1.8
2115XP	45632130	34 – 285	370	15,000	1,500	1.13	151	1/4"	10	1.9	8.0	94.0	7.5/1.8
2168	48806600	20 – 217	271	8,500	1,600	1.27	196	1/4"	10	1.4	9.0	90.0	5.2/1.0
2015MAX	45533735	61 – 190	244	7,100	2,100	1.54	332	1/4"	10	1.6	9.0	96.6	17.4/3.0
212	01343151	27 – 170	244	10,000	1,500	1.31	152	1/4"	10	1.2	5.2	97.5	6.5/1.0
211	01343235	17 – 170	204	10,000	1,500	1.09	168	1/4"	10	1.2	5.2	104.0	5.9/1.6
LA158	49825870	7 – 100	136	10,000	1,400	1.25	137	1/4"	10	1.9	7.5	88.4	3.3/1.1
2102XP	16619686	34 – 54	68	11,000	1,250	0.63	165	1/4"	10	0.8	8.6	85.8	4.4/0.8
1/4" ■													
2101XP	16599466	34 – 54	68	11,000	1,250	0.63	165	1/4"	10	0.8	8.6	85.8	4.4/0.8

(1) ISO28927 – 3-axis measurement: vibration level/measurement uncertainty.